AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
ENGINEERING – MANUFACTURING

P.O. BOX 265
OGDENSBURG
NEW YORK
13669
(315) 472-5270

BOX 5120, STN. "F"
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802
TELEX: 053-4591

SPECIFICATIONS

MODEL AVX-D-3-KS2A (MOD)

Model designation:	AVX-D-3-KS2A (MOD)
Delay range:	Range: 1 — Delay msec (±5%): 5-14 Range: 2 — Delay msec (±5%): 14-24 Range: 3 — Delay msec (±5%): 24-34 Range: 4 — Delay msec (±5%): 34-44 Range: 5 — Delay msec (±5%): 44-53 Range: 6 — Delay msec (±5%): 53-61
Duty cycle:	Will operate to at least 90% of period
Max delay versus PRF:	PRF (Hz) / PERIOD (msec) / MAX DELAY (msec): 15 / 66.67 / 59.99 20 / 50.0 / 45.0 30 / 33.33 / 29.99
Jitter:	≤ ±1 nsec
Input PW:	50 to 500 nsec
Output PW:	2 usec
Signal amplitudes:	TTL level (+5 volts) Output will drive 50 ohm loads
Power requirements:	+28 volts, 200 mA
Connectors:	SMA

05.31.89