



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
Fax: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AV-1011B1-B
Type: High-Speed Pulse Generator
S.N.: 14096
Date: January 14, 2021

Output Amplitude: up to $\pm 100V$, to 50 Ω
Pulse Width (FWHM): 100 ns – 1 ms
Rise Time (20%-80%): ≤ 2 ns
Fall Time (80%-20%): varies
PRF: 1 Hz - 100 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →


Test Waveforms

10 kHz, > +100V, 100 ns, to 50 Ohms,

10 kHz, > -100V, 100 ns, to 50 Ohms,


20 ns/div. 50 V/div (50 mV/div \times 60 dB):

20 ns/div. 50 V/div (50 mV/div \times 60 dB):



10 Hz, > +100V, 1 ms, to 50 Ohms,

200 us/div. 50 V/div:



10 Hz, > -100V, 1 ms, to 50 Ohms,

200 us/div. 50 V/div:

