



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-9A-B-P1B-T1B-P-BAA  
Type: Ultra-High-Speed Laser Diode Driver  
S.N.: 12165  
Date: December 2, 2008



Output Amplitude: 0 to +28V, to 50Ω  
Pulse Width (FWHM): 0.8 – 2.5 ns  
Rise Time (20%-80%): ≤ 300 ps  
Fall Time (80%-20%): ≤ 300 ps  
PRF: 1 Hz - 50 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

Pulse into 50 Ohm load at 50 kHz, 2.5 ns, +28V,  
1 ns/div. 5 V/div (50 mV × 40 dB):

Pulse into 50 Ohm load at 50 kHz, 0.8 ns, +28V,  
1 ns/div. 5 V/div (50 mV × 40 dB):



“MI” output of AVX-S1-P1B-T1B into 50 Ohms, for +28V, 50 kHz, 2.5 ns pulse width, with a 1N4148 test diode installed in the output sockets:

1 ns/div. 0.5 V/div (50 mV × 20 dB, ≈ 105 mA/div):

