



P.O. BOX 265 OGDENSBURG, NY U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl) FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE OTTAWA, ONTARIO CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVOZ-D2-B-AC03-TNT-PN
Type: High-Voltage, High-Current Pulse Generator
S.N.: 12427
Date: April 29, 2010

Positive Test




29 Apr 2010 14:32:55

OUT P, +700V, 10 us, 50 Hz, into one of five attached 50Ω loads.

- a) Output Signal Amplitude: 0 to ±700V, to ≥ 10 Ohms
b) Pulse Width (FWHM): 200 ns – 10 us
c) Rise Time (20%-80%): < 100 ns
d) Fall Time (80%-20%): < 100 ns
e) PRF: 1 Hz – 2.5 kHz
f) Jitter, Stability: OK
g) Prime Power: 100-240V AC, 50-60 Hz.

Negative Test



29 Apr 2010 14:34:47

OUT N, -700V, 10 us, 50 Hz, into one of five attached 50Ω loads.

References levels: 20%, 80%.