



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET


Model: AVR-3HF-B-PN-UWA-CSA  
Type: High Voltage Pulse Generator  
S.N.: 12838  
Date: June 21, 2012

Rise & Fall Time Tests



10 Hz, 500 ns, +50 / +100 / +150 / +200 / +250 V  
into a 50Ω load. 50 V/div, 100 ns/div.


- a) Output Signal Amplitude: up to ±250V
- b) Pulse Width (FWHM): 100 ns - 100 us, 4% duty cycle
- c) Rise Time (20%-80%): < 25 ns
- d) Fall Time (20%-80%): < 25 ns
- e) PRF: 1 Hz - 100 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.




10 Hz, 500 ns, -50 / -100 / -150 / -200 / -250 V  
into a 50Ω load. 50 V/div, 100 ns/div.

References levels: 20%, 80%.

## Wide Pulse Tests



10 Hz, 100 us, +250V into a 50Ω load.  
50 V/div, 20 us/div.



10 Hz, 100 us, -250V into a 50Ω load.  
50 V/div, 20 us/div.